



## VAPCO PRODUCTS, INC.

### Safety Data Sheet No Sweat

---

#### SECTION 1: Identification

##### GHS Product identifier

Product name	No Sweat
Product number	NS-1
Brand	Vapco

##### Recommended use of the chemical and restrictions on use

Pipe Insulation Coating

##### Supplier's details

Name	Vapco Products, Inc.
Address	401 Marshall Road Valley Park, Missouri 63088 United States
Telephone	(636) 923-2121
Fax	(636) 923-3002
email	info@VapcoProducts.com

##### Emergency phone number

(800) 255-3924

---

#### SECTION 2: Hazard identification

##### Classification of the substance or mixture

##### GHS classification in accordance with: OSHA (29 CFR 1910.1200)

- Carcinogenicity, Cat. 1A
- Eye damage/irritation, Cat. 2A
- Flammable aerosols, Cat. 2
- Gases under pressure, liquefied gas

## Safety Data Sheet

- Skin corrosion/irritation, Cat. 2
- Specific target organ toxicity (repeated exposure), Cat. 2
- Specific target organ toxicity (single exposure), Cat. 3

### GHS label elements, including precautionary statements

#### Pictogram



#### Signal word

**Danger**

#### Hazard statement(s)

H223	Flammable aerosol
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H373	May cause damage to organs through prolonged or repeated exposure

#### Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash hands and other exposed areas thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water and get medical attention.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see First Aid on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to the specifications of local, regional, national, and international regulations.

# Safety Data Sheet

## SECTION 3: Composition/information on ingredients

### Mixtures

#### Hazardous components

##### 1. Dichloromethane

Concentration	30 - 60 % (weight)
EC no.	200-838-9
CAS no.	75-09-2
Index no.	602-004-00-3

##### 2. Petroleum gases, liquefied, sweetened, if they contain > 0.1% w/w Butadiene

Concentration	15 - 40 % (weight)
EC no.	270-705-8
CAS no.	68476-86-8
Index no.	649-203-00-1

## SECTION 4: First-aid measures

### Description of necessary first-aid measures

General advice	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
If inhaled	First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Get medical advice/attention.
In case of skin contact	Immediately drench affected area with water for at least 15 minutes. Remove contaminated clothing immediately. Obtain medical attention if irritation develops or persists.
In case of eye contact	Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.
If swallowed	Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### Most important symptoms/effects, acute and delayed

#### Acute Health Hazards

**Symptoms/Injuries:** Harmful if inhaled. Causes serious eye irritation. May cause drowsiness and dizziness. Asphyxia by lack of oxygen: risk of death.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms. Inhalation is likely to cause adverse health effects including, but not limited to: irritation, difficulty breathing, and unconsciousness. In elevated concentrations, may cause asphyxiation, central nervous system effects, and increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death. This product contains chlorinated solvent material, which is associated with cardiac sensitization following very high exposures or

## Safety Data Sheet

with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine and catecholamines. Careful consideration should be applied preceding administration of epinephrine or similar heart-stimulating substances.

**Symptoms/Injuries After Skin Contact:** Contact with gas/liquid escaping the container can cause dermatitis and defatting.

**Symptoms/Injuries After Eye Contact:** Contact causes mild irritation with redness, tearing, and blurred vision.

**Chronic Health Hazards:** Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, lungs, blood, or central nervous system.

### Indication of immediate medical attention and special treatment needed, if necessary

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand. Note to physician: Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This product contains ingredients that may be anticipated to be a carcinogen.

---

## SECTION 5: Fire-fighting measures

### Suitable extinguishing media

Dry chemical, foam, or carbon dioxide (CO<sub>2</sub>). Use appropriate media for surrounding fire.

### Specific hazards arising from the chemical

**Explosion Hazard:** Container may explode in heat of fire. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

**Incompatibilities:** Reacts with some plastics, strong oxidizing agents, acids, caustics, alkalis, and chemically active metals (e.g. aluminum, magnesium, sodium, potassium, and lithium). Increased risk of fire or explosion. Certain mixtures of chlorinated solvents may be flammable or reactive under certain conditions. Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

### Special protective actions for fire-fighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use dry chemical, foam, or carbon dioxide (CO<sub>2</sub>). Do not breathe fumes from fire or vapors from decomposition. Do NOT fight fire when fire reaches containers. Evacuate area. Fight fire remotely due to the risk of explosion. Shut off all sources of ignition. Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. Wear NIOSH-approved Self-Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

**Hazardous Combustion Products:** Oxides of carbon, hydrogen chloride, and phosgene.

### Further information

Do not allow run-off from fire fighting to enter drain or water courses.

---

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapors, spray, mist, gas. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

#### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedure:** Eliminate ignition source first, then ventilate the area. Evacuate unnecessary personnel, isolate, and ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of

## Safety Data Sheet

dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### Environmental precautions

Prevent entry into sewers and public waters. Avoid release to the environment.

### Methods and materials for containment and cleaning up

**For Containment:** Ventilate area. Contain any spills with dikes or absorbents to prevent further migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Eliminate all ignition sources. Ventilate area. Stop the ignition source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Take up liquid spill into absorbent material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

**Waste Disposal:** Dispose of in accordance with local, regional, national, and international regulations. Containers may be hazardous when empty. Do not flame cut, braze, or weld.

### Reference to other sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

---

## SECTION 7: Handling and storage

### Precautions for safe handling

**Additional Hazards When Processed:** Do not pressurize, cut, or weld containers. Ruptured cylinders may rocket. Pressurized container: May burst if heated. Do not pierce or burn, even after use.

**Precautions for Safe Handling:** Do not handle until all safety precautions have been read and understood. Avoid contact with skin, eyes and clothing. Do not breathe gas, mist, spray, vapors. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not spray on open flame or other ignition source.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

**Other Precautions:** Keep out of reach of children. Follow label instructions. Vapors may collect in low lying area.

### Conditions for safe storage, including any incompatibilities

**Technical Measures:** Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

**Storage Conditions:** Store in a dry, cool place. Keep only in the original container in a cool, well-ventilated place away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

**Incompatible Materials:** Reacts with some plastics, strong oxidizing agents, acids, caustics, alkalis, and chemically active metals (e.g. aluminum, magnesium, sodium, potassium, and lithium). Increased risk of fire or explosion. Certain mixtures of chlorinated solvents may be flammable or reactive under certain conditions. Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

**Storage Temperature:** <50°C/122°F.

---

## SECTION 8: Exposure controls/personal protection

### Control parameters

**CAS: 75-09-2 (EC: 200-838-9)**

Dichloromethane

ACGIH (USA): 50 ppm TWA inhalation; Cal/OSHA (USA): 125 ppm, 435 mg/m<sup>3</sup> STEL inhalation; OSHA (USA): 25 ppm PEL inhalation

## Safety Data Sheet

### Appropriate engineering controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Use only outdoors or in well-ventilated area. Ensure all local, regional, national, and international regulations are observed. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

### Individual protection measures, such as personal protective equipment (PPE)

#### Pictograms



#### Eye/face protection

Chemical safety goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.

#### Skin protection

Wear protective gloves and clothing.

#### Body protection

Wear suitable protective clothing. Wear protective gloves. Chemical resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

#### Respiratory protection

Use a NIOSH-approved Self-Containing Breathing Apparatus whenever exposure may exceed established Occupational Exposure Limits.

---

## SECTION 9: Physical and chemical properties and safety characteristics

### Basic physical and chemical properties

Physical state	Liquid
Appearance	Clear Aerosol
Color	N/A
Odor	Chlorinated Solvent Odor
Odor threshold	21 mg/m <sup>3</sup> (Methylene Chloride)
Melting point/freezing point	N/D
Boiling point or initial boiling point and boiling range	> 140°F
Flammability	Flammable Aerosol
Lower and upper explosion limit/flammability limit	N/D
Flash point	N/D
Auto-ignition temperature	N/D
Decomposition temperature	N/D
pH	N/A
Kinematic viscosity	N/D
Solubility	Unsoluble in water
Partition coefficient n-octanol/water (log value)	N/D
Vapor pressure	> 100 mmHg

## Safety Data Sheet

Evaporation rate	> 2
Density and/or relative density	1.2 at 77°F (25°C)
Relative vapor density	> 2 (Air=1)

---

### SECTION 10: Stability and reactivity

#### Reactivity

Stable under normal conditions of use.

#### Chemical stability

Contains gas under pressure; may explode if heated. Pressurized container; may burst if heated.

#### Possibility of hazardous reactions

None known.

#### Conditions to avoid

Excessive heat. Sources of ignition.

#### Incompatible materials

Reacts with some plastics, strong oxidizing agents, acids, caustics, alkalis, and chemically active metals (e.g. aluminum, magnesium, sodium, potassium, and lithium). Increased risk of fire or explosion. Certain mixtures of chlorinated solvents may be flammable or reactive under certain conditions. Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

#### Hazardous decomposition products

Oxides of carbon, hydrogen chloride gas, and phosgene.

---

### SECTION 11: Toxicological information

#### Information on toxicological effects

##### Acute toxicity

Dichloromethane

LD50 Oral - Rat - > 2,000 mg/kg

LC50 Inhalation - Rat - 52,000 mg/m<sup>3</sup>

LD50 Skin - Rat - > 2,000 mg/kg

LC50 - Pimephales promelas (fathead minnow) - 193.00 mg/l - 96 h

##### Skin corrosion/irritation

May cause localized defatting, dryness with prolonged or repeated contact.

##### Serious eye damage/irritation

Causes mild irritation, redness, burning.

##### Respiratory or skin sensitization

Excessive inhalation of vapors may cause irritation of nose and throat. Causes dizziness, headaches, nausea, central nervous system depression, excessive or prolonged exposure may cause unconsciousness.

##### Germ cell mutagenicity

Not classified.

## Safety Data Sheet

### **Carcinogenicity**

Possible cancer causing agents and overexposure may also include damage to skin, kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, lungs, blood, or central nervous system.

### **Reproductive toxicity**

Not classified.

### **STOT-single exposure**

May cause drowsiness or dizziness.

### **STOT-repeated exposure**

Repeated or prolonged exposure may be toxic to kidneys, liver, skin, central nervous system (CNS).

### **Aspiration hazard**

Not classified.

### **Additional information**

#### **Acute Health Hazards**

**Symptoms/Injuries:** Harmful if inhaled. Causes serious eye irritation. May cause drowsiness and dizziness. Asphyxia by lack of oxygen: risk of death.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms. Inhalation is likely to cause adverse health effects including, but not limited to: irritation, difficulty breathing, and unconsciousness. In elevated concentrations, may cause asphyxiation, central nervous system effects, and increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death. This product contains chlorinated solvent material, which is associated with cardiac sensitization following very high exposures or with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine and catecholamines. Careful consideration should be applied preceding administration of epinephrine or similar heart-stimulating substances.

**Symptoms/Injuries After Skin Contact:** Contact with gas/liquid escaping the container can cause dermatitis and defatting.

**Symptoms/Injuries After Eye Contact:** Contact causes mild irritation with redness, tearing, and blurred vision.

**Chronic Health Hazards:** Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, lungs, blood, or central nervous system.

**Medical Condition Aggravated:** Excessive exposure will aggravate pre-existing skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.

---

## SECTION 12: Ecological information

### **Toxicity**

Dichloromethane

LD50 Oral - Rat - > 2,000 mg/kg

LC50 Inhalation - Rat - 52,000 mg/m<sup>3</sup>

LD50 Skin - Rat - > 2,000 mg/kg

LC50 - Pimephales promelas (fathead minnow) - 193.00 mg/l - 96 h

### **Persistence and degradability**

Component or components of this product are not biodegradable.

### **Bioaccumulative potential**

This product is not expected to bioaccumulate.



## Safety Data Sheet

### Mobility in soil

This product is mobile in soil.

---

## SECTION 13: Disposal considerations

### Disposal methods

#### Product disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations. Do not pierce or burn, even after use.

#### Waste treatment

Waste solvent likely considered F001, hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

#### Other disposal recommendations

Container may remain hazardous when empty. Continue to observe all precautions. Do not puncture or incinerate container.

---

## SECTION 14: Transport information

### DOT (US)

UN Number: UN1950

Class: 2.1

Packing Group: N/A

Proper Shipping Name: Aerosols, flammable, n.o.s. (engine starting fluid) (each not exceeding 1 L capacity)

### IMDG

UN Number: UN1950

Class: 2.1

Packing Group: N/A

Proper Shipping Name: Aerosols, flammable, n.o.s. (engine starting fluid) (each not exceeding 1 L capacity)

### IATA

UN Number: UN1950

Class: 2.1

Packing Group: N/A

Proper Shipping Name: Aerosols, flammable, n.o.s. (engine starting fluid) (each not exceeding 1 L capacity)

---

## SECTION 15: Regulatory information

### Safety, health and environmental regulations specific for the product in question

#### California Prop. 65 Components

California Prop. 65 Components

WARNING! This product contains a chemical known to the State of California to cause cancer.

Dichloromethane

CAS number: 75-09-2

#### Canadian Domestic Substances List (DSL)

Chemical name: Methane, dichloro-

CAS: 75-09-2

## Safety Data Sheet

### Massachusetts Right To Know Components

Dichloromethane  
CAS number: 75-09-2

### New Jersey Right To Know Components

Dichloromethane  
CAS number: 75-09-2

### Pennsylvania Right To Know Components

Dichloromethane  
CAS number: 75-09-2

### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Dichloromethane  
CAS number: 75-09-2

### Toxic Substances Control Act (TSCA) Inventory

All chemicals are listed or exempt.

---

## SECTION 16: Other information

N/A = Not applicable; N/D = Not determined

### Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall [COMPANY NAME] be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if [COMPANY NAME] has been advised of the possibility of such damages.

### Preparation information

Prepared by: Jessica Wilson  
Date prepared: 6-22-2022